



(19)

(11) Publication number: **01217921 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**

(21) Application number: 63042351

(51) Intl. Cl.: H01L 21/302

(22) Application date: 26.02.88

(30) Priority:

(43) Date of application  
publication: 31.08.89(84) Designated  
contracting states:(71) Applicant: NIPPON TELEGR & TELEPH CORP  
<NTT>(72) Inventor: URISU TSUNEO  
UCHIUMI YUICHI  
TAKAHASHI JUNICHI


(74) Representative:

**(54) ETCHING METHOD**

(57) Abstract:

**PURPOSE:** To accurately miniaturize by mounting an etching mask on a substrate, supplying etching reaction gas, and irradiating the surface of the substrate with soft X-rays or vacuum ultraviolet rays, thereby etching the irradiated part of the substrate.

**CONSTITUTION:** An optical system 3 for introducing a radiated light L of soft X-rays or vacuum ultraviolet rays from an electron synchrotron light radiating device 1 into a reaction chamber 4 is composed of two planar reflection mirrors 3A, 3B. The material of a substrate 6 to be etched with the light L is made of SiO<sub>2</sub>, Si<sub>3</sub>N<sub>4</sub> or polysilicon added in high concentration with phosphorus or boron. Etching reaction gas G includes small amount of oxygen to be added fluorine and chlorine series etching gas such as SF<sub>6</sub>, CF<sub>4</sub>, SiF<sub>4</sub>, CCl<sub>4</sub>, Cl<sub>2</sub>, XeF<sub>2</sub>, etc. Thus, since the etching for a thin filmlike etching mask 7 made of a material of semiconductor of Si, Ge or metal and their polycrystal scarcely advances even under the irradiation of reaction gas, microminiaturization of 0.1 μm or less can be performed.



COPYRIGHT: (C)1989,JPO&amp;Japio